



by Schneider Electric

# Release Notes

## IPIX IP Cameras Supported on Digital Sentry

Integral Digital Sentry® digital video management systems (DVMS) support certain IPIX® IP camera models. The camera models listed in this document can be used with Digital Sentry IP camera driver 6.8.0.126 and later. Refer to each camera's table for information about the hardware and software features validated for use on a Digital Sentry system. Any general limitations or special instructions are listed at the beginning of the document, and any model-specific information is listed after each table. For information about the general usage of each camera, refer to the camera manufacturer's documentation.

To obtain the latest IP camera driver or documentation for use with Digital Sentry, refer to the Pelco Web site at [www.pelco.com](http://www.pelco.com).

### IPIX CommandView™ Dome CV-D2000

Firmware	N/A
Supported Resolutions	1600 x 1200
Frames per Second (FPS)	1 to 20
Number of Quality Settings	10
Supported Codec	MJPEG
Supported Motion Detection	In-Camera
Pan/Tilt/Zoom (PTZ)	Yes (solid state)

### IPIX CommandView Dome CV-D3000

Firmware	N/A
Supported Resolutions	2048 x 1536
FPS	1 to 12
Number of Quality Settings	10
Supported Codec	MJPEG
Supported Motion Detection	In-Camera
PTZ	Yes (solid state)

## IPIX InSight™ IS-N2000

Firmware	N/A
Supported Resolutions	1600 x 1200
FPS	1 to 17
Number of Quality Settings	10
Supported Codec	MJPEG
Supported Motion Detection	In-Camera
PTZ	Not available

### Contact Information

Pelco Worldwide Headquarters

3500 Pelco Way, Clovis, California 93612 USA

**USA & Canada:** Tel: (800) 289-9100, Fax: (800) 289-9150

**International:** Tel: +1(559) 292-1981, Fax: +1(559) 348-1120

**www.pelco.com**

### Document Revision History

Document #	Date	Comments
C1006RN	1/09	Original version.